



TIGER DRILL PLUS

High Performance Viscosifier

Description

Tiger Drill Plus is a premium liquid co-polymer designed to provide rapid viscosity as well as having long shelf life where the liquid does not separate in the drum over time.

Applications

- Provides fast viscosity
- Stabilizes reactive clays and shales
- Lowers torque and rod chatter
- Reduces friction

Advantages

- Liquid does not separate in the drum and has a long shelf life.
- Liquid is concentrated so provides higher viscosity compared to normal liquid polymers
- Improved core recovery
- Can be used with foam for unconsolidated formations.
- Easy mixing

Typical Properties

Appearance	Milky white liquid
pH (1% Aqueous solution)	7.5 – 8.5

Recommended Treatments

Tiger Drill Plus should be mixed slowly into the circulating system using agitation or a venturi mixer.

- Normal drilling conditions – 1 to 2 litres/m³

Packaging

Tiger Drill comes in 20 L cubes.

Tiger Fluids Pte Ltd | 1 Scotts Road, #24-10 Shaw Centre, Singapore 228208

T +65 6300 7476 | E info@tigerfluids.com | www.tigerfluids.com

A new, cost effective approach to drilling fluids

Weights and measurements are approximate. Information contained in this document is a recommendation made by Tiger Fluids Pte Ltd and is concluded from dependable testing and data. Tiger Fluids Pte Ltd makes no warranty of any kind and accepts no responsibility for any results of using this product or information.