



TIGER COAL DRILL

Liquid CBM inhibitor

Description

Tiger Coal Drill is a liquid product designed for easy drilling and mixing.

Applications

Tiger Coal Drill is non-toxic viscosifier that helps protect the coal seam as well as building a tough, semi-impermeable filter cake which improves borehole stability.

Advantages

- Easy mixing
- Rapid increase in viscosity
- Controls fluid loss
- Inhibits hydratable, dispersive shales
- Produces thin, solid filter cake
- Effective in fresh, brackish and saline water based fluid systems
- Aids hole cleaning and core recovery
- Compatible with most other Tiger Fluids additives
- Non-fermenting and environmentally safe

Typical Properties

Appearance

White slurry

Recommended Treatments

Tiger Coal Drill should be mixed slowly into the circulating system using agitation or a venturi mixer.

- Fluid loss control and viscosity – 5 to 10 L/m³

As an addition to a bentonite system.

- 2 to 5L/m³

Packaging

Tiger Coal Drill comes in 18kg drums.

Tiger Fluids Pte Ltd | 1 Scotts Road, #24-10 Shaw Centre, Singapore 228208

T +65 6300 7476 | E info@tigerfluids.com | www.tigerfluids.com

A new, cost effective approach to drilling fluids

Weights and measurements are approximate. Information contained in this document is a recommendation made by Tiger Fluids Pte Ltd and is concluded from dependable testing and data. Tiger Fluids Pte Ltd makes no warranty of any kind and accepts no responsibility for any results of using this product or information.