



TIGER HAMMER OIL 320

Lubricant and cutting oil

Description

Tiger Hammer Oil 320 is a mineral-oil based heavy duty hammer oil in a 320 centipoise ISO grade. It is activated with an extreme pressure, anti-rust and tacky non-drip additive to impart outstanding characteristics in demanding field conditions

Applications

Tiger Hammer Oil 320 is used to increase tool and bit life as well as corrosion prevention for ferrous and non ferrous components. It has strong adhesiveness to rapidly coat and lubricate moving parts.

Advantages

- Excellent protection against wear
- Good water resistance ensures quick separation of water contamination to reduce corrosion
- High resistance to ageing and oxidation induced deterioration preventing build up of sludgy gum on moving components.
- Increases production
- Excellent adhesive properties

Typical Properties

Appearance	Brown liquid
Flash point	>>220 °C

Recommended Treatments

Hole Size	Recommended usage (ltrs per hour)
3.5" to 5"	1.0 to 2.0
5" to 7.5"	2.0 to 2.5
7.5" to 8.5	2.5 to 3.0
8.5" to 8.75"	3.0 to 3.5
8.75" to 20"	3.5 to 7.0

Packaging

Tiger Hammer Oil 320 comes in 25 litre drums.

Tiger Fluids Pte Ltd | 1 Scotts Road, #24-10 Shaw Centre, Singapore 228208

T +65 6300 7476 | E info@tigerfluids.com | www.tigerfluids.com

A new, cost effective approach to drilling fluids

Weights and measurements are approximate. Information contained in this document is a recommendation made by Tiger Fluids Pte Ltd and is concluded from dependable testing and data. Tiger Fluids Pte Ltd makes no warranty of any kind and accepts no responsibility for any results of using this product or information.