



# TIGER FOAM

## Biodegradable Drilling Foam

### Description

Tiger Foam is a biodegradable foaming agent that can be used in various types of drilling applications and used with fresh and brackish water.

### Applications

Tiger Foam can be used in a variety of air drilling applications such as air/foam, air-gel/foam, mist drilling and stiff foams.

### Advantages

- Improves hole cleaning and cuttings removal
- Reduces tendencies of clays to stick together
- Increases hole stability
- Suppresses dust during drilling operation
- Reduces erosion in poorly consolidated formations
- Environmentally friendly and does not pollute.

### Typical Properties

Appearance	Yellow liquid
pH (1% Aqueous solution)	7.5. – 9.5

### Recommended Treatments

**Air Drilling** – For use as a dust suppressant 0.5 – 1.5 litres per m<sup>3</sup> or 0.1 – 0.2% of volume of injected water.

**Foam Drilling** – Added to injection water at a rate of 1.0 to 3.0% to maintain hole stability and increase penetration rate.

**Stiff Foam Drilling** – For unconsolidated formations, large diameter holes and loss circulation zones, a stiff foam can be used. A slurry of Tiger Foam and Tiger Drill can be added in a proportion of;

- Tiger Foam 10 – 15 litres/1000 litres
- Tiger Drill 1 -2 litres/1000 litres

The slurry is then injected into air stream to produce a thick stiff foam.

### Packaging

Tiger Foam comes in 25kg drums.

Tiger Fluids Pte Ltd | 1 Scotts Road, #24-10 Shaw Centre, Singapore 228208

T +65 6300 7476 | E [info@tigerfluids.com](mailto:info@tigerfluids.com) | [www.tigerfluids.com](http://www.tigerfluids.com)

*A new, cost effective approach to drilling fluids*

Weights and measurements are approximate. Information contained in this document is a recommendation made by Tiger Fluids Pte Ltd and is concluded from dependable testing and data. Tiger Fluids Pte Ltd makes no warranty of any kind and accepts no responsibility for any results of using this product or information.