



TIGER KWIK SEAL

Loss Circulation Material

Description

Tiger Kwik Seal is a blend of flake, fibrous and granular designed to plug loss circulation zones in varying conditions.

Applications

Kwik Seal is used to control or eliminate loss circulation in fractured, high permeable or unconsolidated zones. There are 3 grinds available which can be used depending on loss circulation conditions.

Coarse grind: Used to seal large fractures and can be pumped through large jets or open pipe.

Medium grind: Used to seal medium to fine fractures and porous zones and can be pumped through most jet bits.

Fine grind: Used in fine fractured zones where seepage loss is a problem.

Advantages

- Forms a strong seal under high and low differential pressures and can stop fluid loss in unconsolidated formations.
- Not easily removed by mud circulation.

Typical Properties

Appearance

Yellow to brown blend of particles

Recommended Treatments

Add 10 to 20kg of Tiger Kwik Seal to 1000 litres of drilling fluid. Tiger Kwik Seal can be added through a hopper or into an agitator.

Packaging

Tiger Kwik Seal comes in 25kg bags..

Tiger Fluids Pte Ltd | 1 Scotts Road, #24-10 Shaw Centre, Singapore 228208

T +65 6300 7476 | E info@tigerfluids.com | www.tigerfluids.com

A new, cost effective approach to drilling fluids

Weights and measurements are approximate. Information contained in this document is a recommendation made by Tiger Fluids Pte Ltd and is concluded from dependable testing and data. Tiger Fluids Pte Ltd makes no warranty of any kind and accepts no responsibility for any results of using this product or information.