



TIGER BEN

Viscosifier

Description

Tiger Ben is a premium grade sodium bentonite formulated to provide viscosity that meets API 13A test specifications.

Applications

Tiger Ben is a viscosifier with filtration control properties to aid in providing bore hole stability.

Advantages

- Provides quick viscosity and lubrication
- Cost effective
- Aids hole cleaning
- Reduces fluid loss
- Deposits thin filter cake on bore walls to improve borehole stability
- Compatible with most other Tiger Fluids additives
- Environmentally safe

Typical Properties

Appearance	Grey to tan powder
pH (1% Aqueous solution)	8.0 – 9.0

Recommended Treatments

Tiger Ben should be mixed slowly into the circulating system using agitation or a venturi mixer.

- Normal drilling conditions – 0 to 60kg/m³
- Unconsolidated formations –60 to 80kg/m³

For optimum yield, pre-treat make up water with soda ash to achieve pH of 8 to 9 using approximately 1 to 1.25kg/m³.

Packaging

Tiger Ben comes in 25kg sacks.

Tiger Fluids Pte Ltd | 1 Scotts Road, #24-10 Shaw Centre, Singapore 228208

T +65 6300 7476 | **E** info@tigerfluids.com | www.tigerfluids.com

A new, cost effective approach to drilling fluids

Weights and measurements are approximate. Information contained in this document is a recommendation made by Tiger Fluids Pte Ltd and is concluded from dependable testing and data. Tiger Fluids Pte Ltd makes no warranty of any kind and accepts no responsibility for any results of using this product or information.